



TEST WELL  
BUILD WELL

**WRITTEN EXAMINATION FOR OPERATOR  
QUALIFICATION WINDSOR PROBE TEST SYSTEM**

**Circle Correct Answer**

- True False 1. The Windsor Probe Test System should be used only as prescribed in the Instruction Manual.
- True False 2. Windsor Probe should not be driven closer than 4" from the unsupported edge of concrete.
- True False 3. You must wait one minute between firing the device
- True False 4. The operator can vary the power of the Driver by pushing the probe and driver head further down the barrel.
- True False 5. The PRS-03 (gold colored) is used for lightweight concrete. It has no step diameter at the pointed end.
- True False 6. It is fine to fire the driver without a probe in the barrel.
- True False 7. A driver head is furnished with each kit. It is not necessary to screw the driver head on to the probe to use
- True False 8. You can fire the device on a ladder.
- True False 9. You can load more than one probe at a time
- True False 10. You should never point this device at yourself or others.
- True False 11. The Moh's Scale is a universally accepted method for measuring rock hardness by a scratch test technique.
- True False 12. A probe that does not embed in the concrete means the concrete is over 110 MPA (17000 PSI).
- True False 13. The driver should always be stored unloaded, even during work breaks
- True False 14. The device should only use charges from James Instruments
- True False 15. Windsor cannot be used on concrete over one year old or newly poured concrete three days old.

Signed:

Name (Print )

Affiliation

Address:

3727 N. Kedzie Ave.  
Chicago, IL 60618-4545  
USA

Phone USA: 1-800-426-6500  
Phone Int'l: +1-773-463-6565  
Fax: +1-773-463-0009  
Email: [info@ndtjames.com](mailto:info@ndtjames.com)  
<http://www.ndtjames.com>

© 2020 James Instruments Inc.



Strength Locators Ultrasonics Corrosion Moisture